



Cover Type:	Special polyurethane	
Possible applications:	Rollers in high temperature environment, combined with high load and/or abrasion - rollers at high temperature and in contact with oily products Rollers at entry and exit of dryers, ovens and furnaces Aluminium industry : ironing rollers for cold rolling mills - Steel industry : skin-pass squeegee rollers	
Hardness Range:	90 Shore A	
Available Colours:	brown	
Recommended Cover Thickness:	min. 10 mm - max. 20 mm	
Temperature resistance:	Dry:	continuous 110°C / peak 130°C
	Wet:	continuous 50°C / peak 60°C
Properties and advantages:	Polyurethane solution with high (dry) temperature resistance Superior mechanical and dynamical properties, excellent abrasion resistance Excellent resistance to oil, fuel, kerosene and grease	
Chemical resistance:	Acid solutions:	Not suited
	Alkaline solutions:	Not suited
	Hot water and steam:	Not suited
	Ozone:	Good
	Oil and grease:	Excellent
	Aromatic solvents (toluene, benzene,...):	Moderate
	Chlorinated solvents:	Moderate
	Polar solvents (MEC, ether, acetate,...):	Not suited
Recommended cleaning products:	(Tepid) water, soap, industrial cleaners, cleaning fuel, terpineol, with limited use : alcohol	