

# MetalSqueeze-XP



<b>Cover Type:</b>	Special rubber
<b>Possible applications:</b>	Steel, aluminium and non ferrous strip processing : squeegee, hold-down and sink rolls in all chemical environments (pickling, cleaning, electrolytical processes, passivation...)  Stainless steel strip processing : specifically recommended for mixed acid pickling  Metals industry : bridle rollers, oven exit rollers, all rollers in or in proximity of drying and oven sections
<b>Hardness Range:</b>	60, 65, 70, 75, 80, 85, 90 Shore A
<b>Available Colours:</b>	black
<b>Recommended Cover Thickness:</b>	min. 15 mm - max. 25 mm
<b>Temperature resistance:</b>	Dry: continuous 125°C / peak 140°C Wet: continuous 85°C / peak 95°C
<b>Properties and advantages:</b>	Very good physical properties, abrasion resistance and cut-in resistance  Very high resilience, excellent compression set, excellent squeezing behaviour  Excellent resistance to most alkaline, acid and oxydative products, even at high concentration  Excellent temperature resistance  Moderate oil resistance
<b>Specific characteristics:</b>	Antistatic
<b>Chemical resistance:</b>	Acid solutions: Excellent Alkaline solutions: Very good Hot water and steam: Very good Ozone: Very good Oil and grease: Moderate Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Moderate
<b>Recommended cleaning products:</b>	(Hot) water, acid and alkaline cleaners, soap and detergents, alcohol based cleaners