



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	Squeegee and sink rollers for the pickling and acid treatment of stainless steel strip  Specifically recommended for HF/HNO <sub>3</sub> environment
<b>Hardness Range:</b>	75 Shore A
<b>Available Colours:</b>	black
<b>Recommended Cover Thickness:</b>	min. 15 mm - max. 25 mm
<b>Temperature resistance:</b>	Dry: continuous 120°C / peak 130°C Wet: continuous 90°C / peak 95°C
<b>Properties and advantages:</b>	Special rubber compound with very high chemical resistance to most concentrated acids and oxydative products  Specifically resistance to HF/HNO <sub>3</sub> mixtures used in the stainless steel industry, resistant tot H <sub>2</sub> O <sub>2</sub> injections  Non staining, suited for stainless steel bright annealing
<b>Chemical resistance:</b>	Acid solutions: Excellent Alkaline solutions: Very good Hot water and steam: Excellent Ozone: Excellent Oil and grease: Not suited Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Very good Alcohols (ethanol, IPA,...): Excellent
<b>Recommended cleaning products:</b>	(Hot) water, acid and alkaline cleaners, IPA and alcohol, MEC, ether, ethyl acetate