

# MultiGraf-SB-AS



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	Production and conversion of plastic film, PVC, flexible packaging, (card)board, tape, labels, adhesives and aluminium foil  Back-up rollers for solventless and solvent based coating and lamination processes  Rotogravure impression rollers for flexible packaging and décor printing
<b>Hardness Range:</b>	60, 65, 70, 75, 80, 85, 90 Shore A
<b>Available Colours:</b>	black
<b>Recommended Cover Thickness:</b>	min. 12 mm - max. 20 mm
<b>Temperature resistance:</b>	Dry: continuous 110°C / peak 125°C Wet: continuous 80°C / peak 90°C
<b>Properties and advantages:</b>	Excellent resistance to polar solvents (MEK, ethyl acetate, alcohols)  Outstanding surface properties in contact with various web types : paper, board, plastic film, aluminium  Very good overall physical properties and abrasion resistance  High purity and homogeneity  Good antistatic properties
<b>Specific characteristics:</b>	Antistatic
<b>Chemical resistance:</b>	Acid solutions: Very good Alkaline solutions: Very good Hot water and steam: Very good Ozone: Excellent Oil and grease: Not suited Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Excellent
<b>Recommended cleaning products:</b>	Polar solvents (MEK, ethyl acetate, alcohol...), detergents - avoid hydrocarbons !