

# HanneFood-XP



<b>Cover Type:</b>	Special polyurethane
<b>Possible applications:</b>	Rollers for direct or indirect contact with food, sieve press and transport rolls for the food industry Rollers in converting industries, where food grade and/or sanitary properties are required
<b>Hardness Range:</b>	60, 70, 80, 90 Shore A
<b>Available Colours:</b>	white
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 20 mm
<b>Temperature resistance:</b>	Dry: continuous 70°C / peak 90°C Wet: continuous 50°C / peak 60°C
<b>Properties and advantages:</b>	Suited for food contact – see details below High purity and homogeneity Excellent resistant to mineral oils, to greasy substances, to vegetal oils and animal fats Good resistance to most cleaning products Very good physical properties, tear and abrasion resistance
<b>Specific characteristics:</b>	Food approved
<b>Chemical resistance:</b>	Acid solutions: Moderate Alkaline solutions: Good Hot water and steam: Moderate Ozone: Good Oil and grease: Very good Aromatic solvents (toluene, benzene,...): Moderate Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Not suited Alcohols (ethanol, IPA,...): Good
<b>Recommended cleaning products:</b>	(Tepid) water, soap, industrial cleaners, IPA, with limited use : other alcohol-based cleaners
<b>Remark:</b>	Food grade compliant to : - FDA CFR 21 part 177-2600 (Test reports Ianesco n°RE-13/14968 – 14969 – 14970 – 14971)

# HanneFood-XP

- EU regulation 10/2011 concerning the overall migration (Test report lanesco n° 16/10609 - migration in 10% ethanol (simulant A) - 2h/70°C, in 3% acetic acid (simulant B) - 2h/70°C and in vegetable oil (simulant D2) - 2h/70°C)
  - EU regulation 10/2011 concerning the content of 4,4' diphenyl methane diisocyanate (Test report lanesco n° 16/10577-2)
-