Flexolys[®] G



Possible applications:Grooved Press rollHardness Range:5, 10, 15, 20, 25, 30, 35 PJAvailable Colours:greenRecommended Cover Thickness:max. 20 mmTemperature resistance:Dry:Continuous 80°C / peak 110°CProperties and advantages:Long lifetime due to excellent wear resistance without hydrolysis High vibration absorption High performance bonding system Hardness & profile stability in operation
Available Colours: green Recommended Cover Thickness: max. 20 mm Temperature resistance: Dry: continuous 80°C / peak 110°C Properties and advantages: Long lifetime due to excellent wear resistance without hydrolysis High vibration absorption High performance bonding system Hardness & profile stability in operation
Recommended Cover Thickness: max. 20 mm Temperature resistance: Dry: continuous 80°C / peak 110°C Properties and advantages: Long lifetime due to excellent wear resistance without hydrolysis High vibration absorption High performance bonding system Hardness & profile stability in operation
Temperature resistance: Dry: continuous 80°C / peak 110°C Properties and advantages: Long lifetime due to excellent wear resistance without hydrolysis High vibration absorption High performance bonding system Hardness & profile stability in operation
Properties and advantages: Long lifetime due to excellent wear resistance without hydrolysis High vibration absorption High performance bonding system Hardness & profile stability in operation
High vibration absorption High performance bonding system Hardness & profile stability in operation
Limited energy losses due to very low heat buildup Tailor made surface design for dewatering optimization
Doctoring:HDPE blade at 1 to 2 mm from surface or 18 deg & 50 to 70 N/m if loaded, HDPE foil blade 10 deg, 50 to 70 N/m Dry doctoring is prohibited
Possible surface design: P (Plain), S (Suction), BD (Blind Drilled), G (Grooved) & combined SBD, SG, SBDG, BDG
Max. linear load: Depending on operating conditions and nip rolls Ø (to be validated by Hanne in case of doubt)
Chemical resistance: Acid solutions: Moderate Alkaline solutions: Moderate Hot water and steam: Very good Ozone: Very good Oil and grease: Good Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,): Not suited
Recommended cleaning products: Good resistance to standard chemicals normally used in paper
Remark: Reference list available on demand

