

# HanneStar Plus



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	Rollers submitted to mechanical load and in contact with oil or grease of mineral and animal origin, also at higher temperature.  Areas of application : metal and aluminium industry, conveyor systems, food and meat processing, wood industry, conversion of PVC and plastic film etc.
<b>Hardness Range:</b>	65, 70, 80, 85, 92, 95, 97 Shore A
<b>Available Colours:</b>	black
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 20 mm
<b>Temperature resistance:</b>	Dry: continuous 100°C / peak 110°C Wet: continuous 70°C / peak 80°C
<b>Properties and advantages:</b>	Very good physical properties, good tear and cut-in resistance  Excellent resistance to mineral, vegetable and synthetic oils. Very good resistance to kerosine and fuels  Good resistance to diluted acids and to alkaline solutions
<b>Chemical resistance:</b>	Acid solutions: Good Alkaline solutions: Good Hot water and steam: Good Ozone: Very good Oil and grease: Excellent Aromatic solvents (toluene, benzene,...): Moderate Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Not suited
<b>Recommended cleaning products:</b>	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, turpentine, white spirit