


# MultiCoat-SP



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	Wood and wood laminate, PVC flooring production : varnishing rollers, glue applicators  Conversion of paper and film – adhesive and release stock : primer, glue and silicone applicator rollers and sleeves  All converting of (printed) paper, board, film and flexible packaging : applicator, coater and (UV) varnishing rollers and sleeves, backing rollers and sleeves
<b>Hardness Range:</b>	30, 40, 50, 60, 70 Shore A
<b>Available Colours:</b>	grey
<b>Recommended Cover Thickness:</b>	min. 15 mm - max. 30 mm
<b>Temperature resistance:</b>	Dry: continuous 80°C / peak 110°C Wet: continuous 90°C / peak 125°C
<b>Properties and advantages:</b>	Good physical properties  Excellent resistance to polar solvents (MEC, acetates, alcohols...)  Very good surface wetting and transfer properties  High purity and homogeneity
<b>Chemical resistance:</b>	Acid solutions: Very good Alkaline solutions: Very good Hot water and steam: Very good Ozone: Excellent Oil and grease: Not suited Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Excellent
<b>Recommended cleaning products:</b>	(Warm) water, soap, detergent, acid/alkaline cleaners, polar solvents : MEK, alcohol, acetate...