

MultiCoat-SB-AS



Cover Type:	Rubber
Possible applications:	Metals and metal packaging industry : applicator rollers and wheels for primer coating, lacquering, varnishing and chemical coating Wood and wood laminate : varnishing rollers, glue applicators Conversion of paper and film – adhesive and release stock : primer, glue and silicone applicator rollers and sleeves All converting of (printed) paper, board, film and flexible packaging : applicator, coater and (UV) varnishing rollers and sleeves, backing rollers and sleeves
Hardness Range:	35, 50, 55, 60, 65, 70, 75 Shore A
Available Colours:	black
Temperature resistance:	Dry: continuous 110°C / peak 125°C Wet: continuous 80°C / peak 90°C
Properties and advantages:	Good physical properties Excellent resistance to polar solvents (MEC, acetates, alcohols...) Very good surface wetting and transfer properties High purity and homogeneity Easy to grind and to groove Antistatic
Specific characteristics:	Antistatic
Chemical resistance:	Acid solutions: Very good Alkaline solutions: Very good Hot water and steam: Very good Ozone: Excellent Oil and grease: Not suited Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Excellent
Recommended cleaning products:	(Warm) water, soap, detergent, acid/alkaline cleaners, polar solvents : MEK, alcohol, acetate...