Optidraw Plus



Cover Type:	Rubber		
Possible applications:	Production of metal strip : pinch rolls, hold-down rolls, steering, bridle and detour rolls, conveyor rollers, oil distribution and wipe-off rolls, squeegee rolls in different environments		
	Diverse applications in a lot of ir plastic film, converting, glass, w	ndustrial areas : textile, packaging, (card)board, rood etc.	
	Rollers and wheels in contact w	ith oil, fuel or grease, even at higher temperature	
	Finishing of the roller with peach	h skin	
Hardness Range:	65 Shore A		
Available Colours:	beige		
Recommended Cover Thickness:	min. 10 mm - max. 25 mm		
Temperature resistance:	Dry: Wet:	continuous 90°C / peak 110°C continuous 60°C / peak 80°C	
Properties and advantages:	Excellent resistance to mineral and vegetal oil, fuel, grease and (animal) fat		
	Excellent properties, tear and abrasion resistance, good elasticity and resilience		
	Non-staining in contact with delicate substrates		
	Very good and stable grip in contact with most substrates		
	Very good squeegee and wipe-off behavior		

Chemical resistance:	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,): Chlorinated solvents: Polar solvents (MEC, ether, acetate,):	Good Very good Good Good Excellent Good Not suited Not suited
Recommended cleaning products:	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, terpentine, white spirit	



Optidraw Plus

