NipFoil-D



| Cover Type: | Rubber | | |
|--------------------------------|--|--|--|
| Possible applications: | Production of plastic film, adhesives and flexible packaging : conveyor, contact and lay-on rollers for winding | | |
| Hardness Range: | 65, 80 Shore A | | |
| Available Colours: | black | | |
| Recommended Cover Thickness: | Standard 15 mm | | |
| Temperature resistance: | | continuous 110°C / peak 130°C continuous 80°C / peak 90°C | |
| Properties and advantages: | Special double layer technology with very soft base layer to reduce wrinkle formation during winding Harder outside layer assures good abrasion resistance and long lifetime | | |
| | Entirely antistatic Good and neutral behavior in contact with plastic film | | |
| Specific characteristics: | Antistatic | | |
| Chemical resistance: | Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,): Chlorinated solvents: Polar solvents (MEC, ether, acetate,): Alcohols (ethanol, IPA,): Ageing resistance: | Excellent Excellent Very good Excellent Not suited Not suited Not suited Excellent Excellent Excellent | |
| Recommended cleaning products: | (Hot) water, acid and alkaline cleaners, IPA and alcohol, MEC, ether, ethyl acetate | | |

HANNECARD YOUR ROLLER EXPERT

Print date: 18/05/2024