

# WoodCoat-SP



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	Production of wood, wood board and wood laminate : - varnishing and lacquering rollers for water or oil based coatings - oiling and staining rollers - impregnation rollers - catalyst and primer application  Possibility to foresee microgrooves up to 80 grooves/inch
<b>Hardness Range:</b>	40, 45, 50, 55, 60, 65, 70, 80 Shore A
<b>Available Colours:</b>	black
<b>Recommended Cover Thickness:</b>	min. 12 mm - max. 25 mm
<b>Temperature resistance:</b>	Dry: continuous 100°C / peak 110°C Wet: continuous 60°C / peak 70°C
<b>Properties and advantages:</b>	Very good surface wetting and transfer properties  Good physical properties and lifetime  High purity and homogeneity  Excellent oil resistance  Easy to grind and to groove
<b>Chemical resistance:</b>	Acid solutions: Moderate Alkaline solutions: Good Hot water and steam: Good Ozone: Very good Oil and grease: Exceptional Aromatic solvents (toluene, benzene,...): Moderate Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Not suited Alcohols (ethanol, IPA,...): Very good Ageing resistance: Excellent
<b>Recommended cleaning products:</b>	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, terpentine, white spirit