

# WoodBond-XP



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	Production of wood, wood board and wood laminate : - applicator and transfer rollers for cold glue, water or formaldehyde based - applicator rollers for hardeners and catalysts
<b>Hardness Range:</b>	60, 65, 70, 80 Shore A
<b>Available Colours:</b>	black
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 20 mm
<b>Temperature resistance:</b>	Dry: continuous 120°C / peak 130°C Wet: continuous 80°C / peak 90°C
<b>Properties and advantages:</b>	Good surface wetting and transfer properties Excellent physical properties and lifetime High purity and homogeneity
<b>Chemical resistance:</b>	Acid solutions: Excellent Alkaline solutions: Excellent Hot water and steam: Excellent Ozone: Excellent Oil and grease: Moderate Aromatic solvents (toluene, benzene,...): Moderate Chlorinated solvents: Moderate Polar solvents (MEC, ether, acetate,...): Moderate Alcohols (ethanol, IPA,...): Very good Ageing resistance: Excellent
<b>Recommended cleaning products:</b>	(Hot) water, acid and alkaline cleaners, soap and detergents, alcohol based cleaners