

# Bacroll



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	Textile industry - sizing of yarns : dip and squeeze rollers Recommended solution for the dip roller postions
<b>Hardness Range:</b>	62, 69, 79 Shore A
<b>Available Colours:</b>	black
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 20 mm
<b>Temperature resistance:</b>	Dry: continuous 105°C / peak 115°C Wet: continuous 90°C / peak 100°C
<b>Properties and advantages:</b>	Very good chemical resistance to sizing products, both for natural as for synthetic yarns, up to 100 °C  Very good mechanical properties, abrasion and tear resistance  Non-staining
<b>Chemical resistance:</b>	Acid solutions: Moderate Alkaline solutions: Very good Hot water and steam: Very good Ozone: Excellent Oil and grease: Excellent Aromatic solvents (toluene, benzene,...): Moderate Chlorinated solvents: Moderate Polar solvents (MEC, ether, acetate,...): Not suited Alcohols (ethanol, IPA,...): Very good Ageing resistance: Excellent
<b>Recommended cleaning products:</b>	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, terpentine, white spirit
<b>Remark:</b>	Bacroll-HP : special multi-layer solution for high load applications