

Reversmaster 3



Cover Type:	Rubber
Possible applications:	Adhesives industry, production of tape and label stock : transfer & applicator rollers & sleeves for silicone coating, applicator and backing rollers for primer coating, cold glue coating Plastic film & packaging industry : coating rollers for water and solvent based coating
Hardness Range:	70, 80 Shore A
Available Colours:	black
Recommended Cover Thickness:	min. 12 mm - max. 25 mm
Temperature resistance:	Dry: continuous 100°C / peak 120°C Wet: continuous 70°C / peak 80°C
Properties and advantages:	Low surface energy, low surface roughness Good abrasion resistance Dimensional stability throughout the complete lifetime, constant and homogeneous coating quality Very good chemical compatibility, specifically adapted to polar solvents (MEC, ethyle acetate...)
Chemical resistance:	Acid solutions: Very good Alkaline solutions: Very good Hot water and steam: Very good Ozone: Very good Oil and grease: Not suited Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Excellent Alcohols (ethanol, IPA,...): Excellent Ageing resistance: Excellent
Recommended cleaning products:	Polar solvents (MEK, ethyl acetate, alcohol...), detergents - avoid hydrocarbons !