



<b>Cover Type:</b>	Special rubber	
<b>Possible applications:</b>	<p>Steel industry : preferred solution for hold-down, pressure and squeegee rollers on chrome plating lines, when high hardness is requested</p> <p>High hardness rubber cover for any environment combining temperature, abrasion, corrosion and pressure</p>	
<b>Hardness Range:</b>	95 Shore A	
<b>Available Colours:</b>	beige	
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 25 mm	
<b>Temperature resistance:</b>	Dry: Wet:	continuous 125°C / peak 140°C continuous 85°C / peak 95°C
<b>Properties and advantages:</b>	<p>Special cover with very high chemical stability in corrosive and oxydative environment, like chromic acid</p> <p>High load resistance</p>	
<b>Chemical resistance:</b>	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...):	Excellent Very good Very good Very good Good Moderate Not suited Not suited
<b>Recommended cleaning products:</b>	(Warm) water, soap, industrial cleaners and detergents, alcohol, acid and alkaline cleaners	