

HannePress



Cover Type:	Special rubber														
Possible applications:	Plain Press roll in contact with Felt, soft smoothing press, Baby press														
Hardness Range:	12, 20, 25, 30, 35, 40, 45, 65 PJ														
Available Colours:	black														
Recommended Cover Thickness:	max. 20 mm														
Temperature resistance:	Dry: continuous 120°C / peak 130°C														
Properties and advantages:	<ul style="list-style-type: none">- water resistance- Impact resistance- Profile and hardness stability in operation														
Internal cooling:	recommended inlet T° of the cooling water : 30 and 45°C Adjust water flow until 5°C < dT < 10°C														
Chemical resistance:	<table><tr><td>Acid solutions:</td><td>Good</td></tr><tr><td>Alkaline solutions:</td><td>Good</td></tr><tr><td>Hot water and steam:</td><td>Good</td></tr><tr><td>Ozone:</td><td>Good</td></tr><tr><td>Oil and grease:</td><td>Excellent</td></tr><tr><td>Chlorinated solvents:</td><td>Not suited</td></tr><tr><td>Polar solvents (MEC, ether, acetate,...):</td><td>Not suited</td></tr></table>	Acid solutions:	Good	Alkaline solutions:	Good	Hot water and steam:	Good	Ozone:	Good	Oil and grease:	Excellent	Chlorinated solvents:	Not suited	Polar solvents (MEC, ether, acetate,...):	Not suited
Acid solutions:	Good														
Alkaline solutions:	Good														
Hot water and steam:	Good														
Ozone:	Good														
Oil and grease:	Excellent														
Chlorinated solvents:	Not suited														
Polar solvents (MEC, ether, acetate,...):	Not suited														
Remark:	- reference list available on demand - good resistance to standard chemicals normally used in paper machines														