Monkal[®]-4



Cover Type:	Special polyurethane		
Possible applications:	Metals industry : applicator rollers for colour coating, lacquering, printing and chemical coating Specifically suited for coatings with critical aspect (metallic coating, clear coat, low coating thickness etc.)		
	 Metal packaging : coating on sheet, beverage cans and spray cans - suited for BPA-free food lacquering Coating on paper, plastic film and aluminium foil : silicone coating, primer coating, varnish, protective coating Coating on wood and wood panels : bonding layers, catalyser or activator, varnish and clear coating, white coating, staining 		
	Silicone, primer and glue coating for the production of release, label and adhesive stock		
	Other roll-coating applications (PVC, textile, non-woven)		
Hardness Range:	40, 45, 50, 52, 55, 60, 65 Shore A		
Available Colours:	beige, green, blue, yellow		
Recommended Cover Thickness:	min. 15 mm - max. 30 mm		
Temperature resistance:	Dry: Wet:	continuous 50°C / peak 80°C continuous 30°C / peak 40°C	
Properties and advantages:	Outstanding surface wetting properties,also for water based products - high surface energy		
	High purity and homogeneity		
	Suitable for use in solvent environment (see specific recommendations) - Thanks to the special filler technology, Monkal-4 shows better stability in contact with solvents than other polyurethane covers		
	Good resistance to abrasion and tear		
	Easy to grind and to groove		
Chemical resistance:	Acid solutions: Alkaline solutions: Hot water and steam: Ozone:	Moderate Moderate Not suited Good	



	Oil and grease: Aromatic solvents (toluene, benzene,): Chlorinated solvents: Polar solvents (MEC, ether, acetate,): Alcohols (ethanol, IPA,):	Very good Moderate Not suited Moderate Good	
Recommended cleaning products:	Water, soap & detergents, fuel, Solvesso, turpentine – with moderation: alcohol based cleaners, MEC		
Remark:	For the correct use of Monkal-4 coated rollers and wheels, we kindly refer to the Monkal Quick Start Manual		

