



Cover Type:	Special cover	
Possible applications:	<p>Production and conversion of plastic film, packaging, non-woven and hygiene products : lamination and embossing counterparts</p> <p>Rollers for coating-lamination, coating-embossing and hot-melt applications</p> <p>Brick packaging production : counterparts for lamination of extruded plastic film on perforated cardboard</p>	
Hardness Range:	65 Shore A	
Available Colours:	grey	
Recommended Cover Thickness:	min. 10 mm - max. 25 mm	
Temperature resistance:	Dry:	continuous 200°C / peak 230°C
	Wet:	continuous 200°C / peak 230°C
Properties and advantages:	<p>Special double layer technology with hard base layer for dynamic properties at high speed and softer outside layer for good deformation</p> <p>Excellent resistance to temperature and ozone</p> <p>Improved release and non-stick properties of the outside layer</p>	
Specific characteristics:	<p>Glue repellent/non-stick properties</p> <p>Improved web release properties</p>	
Chemical resistance:	Acid solutions:	Very good
	Alkaline solutions:	Very good
	Hot water and steam:	Good
	Ozone:	Excellent
	Oil and grease:	Excellent
	Aromatic solvents (toluene, benzene,...):	Very good
	Chlorinated solvents:	Not suited
	Polar solvents (MEC, ether, acetate,...):	Not suited
	Alcohols (ethanol, IPA,...):	Very good
	Ageing resistance:	Excellent
Recommended cleaning products:	All industrial cleaners and solvents, except polar solvents (MEK, ether, acetate)	