



Cover Type:	Polyurethane	
Possible applications:	<p>Rollers and wheels suffering from (very) high load or traction, also at high process speed</p> <p>Tension, bridle, steering, stretching, cradle and snubber rolls for the steel and aluminium industry - specifically suited for the production of aluminium coils (kerosene resistance)</p> <p>Counterparts for cutting, pricking, embossing, stretching and laminating in various industries</p> <p>Heavy load wheels and pulleys</p> <p>Technical components submitted to high load</p>	
Hardness Range:	70, 80, 90, 95 Shore A	
Available Colours:	green, red, brown	
Recommended Cover Thickness:	min. 10 mm - max. 30 mm	
Temperature resistance:	Dry:	continuous 80°C / peak 90°C
	Wet:	continuous 40°C / peak 50°C
Properties and advantages:	<p>Very high load resistance, very good dynamical properties with low heat build-up</p> <p>Remarkable abrasion, cut and tear resistance</p> <p>Excellent resistance to mineral, synthetic and vegetal oil - good resistance against non-polar solvents - excellent resistance to kerosene and fuel</p>	
Chemical resistance:	Acid solutions:	Not suited
	Alkaline solutions:	Not suited
	Hot water and steam:	Not suited
	Ozone:	Good
	Oil and grease:	Excellent
	Aromatic solvents (toluene, benzene,...):	Moderate
	Chlorinated solvents:	Not suited
	Polar solvents (MEC, ether, acetate,...):	Not suited
Recommended cleaning products:	Water, soap & detergents, fuel, Solvesso, turpentine – with moderation: alcohol based cleaners	