

# MetalClean-S



<b>Cover Type:</b>	Rubber	
<b>Possible applications:</b>	<p>Metals industry : sink and squeegee rollers for all alkaline cleaning environments up to 90 °C</p> <p>Metals industry : squeegee, sink, deflector and hold-down rollers for treatment with water, demineralized water, electrolyte solutions and diluted acids</p>	
<b>Hardness Range:</b>	65, 70, 75, 80 Shore A	
<b>Available Colours:</b>	black	
<b>Recommended Cover Thickness:</b>	min. 12 mm - max. 25 mm	
<b>Temperature resistance:</b>	Dry: Wet:	continuous 100°C / peak 110°C continuous 80°C / peak 90°C
<b>Properties and advantages:</b>	<p>Overall good chemical resistance to alkaline, acid and oxydative products</p> <p>Very good resistance to mineral, vegetable and synthetic oils. Good resistance to kerosine and fuels</p> <p>Very good physical properties, specifcally abrasion, tear and cut-in resistance</p> <p>High resilience, excellent squeegee behaviour and efficiency</p>	
<b>Chemical resistance:</b>	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...):	Good Very good Good Very good Very good Moderate Not suited Not suited
<b>Recommended cleaning products:</b>	(Warm) water, Soap, industrial, acid and alkaline detergents, alkohol, fuel-based cleaners	