



Cover Type:	Rubber
Possible applications:	<p>Steel, stainless steel, aluminium and non-ferrous strip processing : squeegee, detour, sink and back-up rollers</p> <p>Specifically suited for HCl and H₂SO₄ pickling, for electrolytical treatments (anodising, zink plating, tin plating,...), for chrome and chrome free passivation and for rinsing, quench and cooling sections</p> <p>Suited for some alkaline cleaning and degreasing environments up to 70 °C</p> <p>Not suited for mixed acid (HF/HNO₃) pickling on stainless steel strip</p>
Hardness Range:	50, 60, 70, 80, 92 Shore A
Recommended Cover Thickness:	min. 15 mm - max. 25 mm
Temperature resistance:	Dry: continuous 120°C / peak 135°C Wet: continuous 75°C / peak 85°C
Properties and advantages:	<p>Excellent physical properties, Very high abrasion, tear and cut-in resistance</p> <p>Very good resistance to most acid solutions and to demineralised water.</p> <p>Fair resistance to alkaline solutions up to 70 °C</p> <p>Good resistance to mineral oil</p> <p>Not recommended for mixed acid environment as used in the pickling process of stainless steel (HF/HNO₃)</p>
Chemical resistance:	Acid solutions: Very good Alkaline solutions: Good Hot water and steam: Good Ozone: Very good Oil and grease: Good Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Not suited
Recommended cleaning products:	(Warm) water, soap, industrial cleaners and detergents, alcohol, (diluted) acid cleaners
Remark:	Brown colour : only 90 shore A