

MultiCoat-XP



Cover Type:	Special rubber	
Possible applications:	<p>Production of steel, aluminium & non-ferrous coils : applicator rollers for chemical coating and for water-based lacquering and coating</p> <p>Adhésives and label stock production : transfer and applicator rollers for siliconizing, glue and primer coating</p> <p>Plastic film, paper and flexible packaging industry : coater and transfer rollers, lamination counterparts</p>	
Hardness Range:	45, 50, 55, 60, 70, 80 Shore A	
Recommended Cover Thickness:	min. 10 mm - max. 30 mm	
Temperature resistance:	Dry: Wet:	continuous 100°C / peak 120°C continuous 60°C / peak 80°C
Properties and advantages:	<p>Excellent abrasion, tear and cut-in resistance</p> <p>High surface energy, very good transfer properties and wettability</p> <p>High purity and homogeneity</p> <p>Very good resistance to water based and acid based coatings</p> <p>Moderate resistance to solvents</p>	
Chemical resistance:	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...): Alcohols (ethanol, IPA,...):	Very good Good Good Excellent Good Not suited Not suited Moderate Very good
Recommended cleaning products:	(Warm) water, soap, industrial cleaners and detergents, alcohol, (diluted) acid cleaners	