

# RollMet-CR



<b>Cover Type:</b>	Special rubber
<b>Possible applications:</b>	Metal strip production : pinch, snubber, detour, traction and bridle rollers - tension rollers for cold rolling mills  Specifically rollers with loss of grip and friction coefficient in time
<b>Hardness Range:</b>	75, 85, 90 Shore A
<b>Available Colours:</b>	black
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 20 mm
<b>Temperature resistance:</b>	Dry: continuous 100°C / peak 110°C Wet: continuous 75°C / peak 85°C
<b>Properties and advantages:</b>	Overall good physical properties and cut resistance  Special filler creating a constant grip and friction coefficient in time  Excellent resistance to oil, fuel and kerosine
<b>Chemical resistance:</b>	Acid solutions: Good Alkaline solutions: Good Hot water and steam: Good Ozone: Very good Oil and grease: Excellent Aromatic solvents (toluene, benzene,...): Moderate Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Not suited Alcohols (ethanol, IPA,...): Very good
<b>Recommended cleaning products:</b>	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, turpentine, white spirit