

# RollMet-CR



<b>Cover Type:</b>	Special rubber	
<b>Possible applications:</b>	Metal strip production : pinch, snubber, detour, traction and bridle rollers - tension rollers for cold rolling mills	
	Specifically rollers with loss of grip and friction coefficient in time	
<b>Hardness Range:</b>	75, 85, 90 Shore A	
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 20 mm	
<b>Temperature resistance:</b>	Dry:	continuous 100°C / peak 110°C
	Wet:	continuous 75°C / peak 85°C
<b>Properties and advantages:</b>	Overall good physical properties and cut resistance	
	Special filler creating a constant grip and friction coefficient in time	
	Excellent resistance to oil, fuel and kerosine	
<b>Chemical resistance:</b>	Acid solutions:	Good
	Alkaline solutions:	Good
	Hot water and steam:	Good
	Ozone:	Very good
	Oil and grease:	Excellent
	Aromatic solvents (toluene, benzene,...):	Moderate
	Chlorinated solvents:	Not suited
	Polar solvents (MEC, ether, acetate,...):	Not suited
	Alcohols (ethanol, IPA,...):	Very good
<b>Recommended cleaning products:</b>	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, terpentine, white spirit	