



Cover Type:	Rubber	
Possible applications:	<p>Production, calendering and embossing of PVC and soft plastics (floor covering, wall paper, clothing, liner, foil, artificial leather, stationary, screens, posters, décor product etc.)</p> <p>Press rolls for (finish) calendering</p>	
Hardness Range:	65, 70, 80, 92 Shore A	
Available Colours:	black	
Recommended Cover Thickness:	min. 15 mm - max. 30 mm	
Temperature resistance:	<p>Dry:</p> <p>Wet:</p>	<p>continuous 90°C / peak 110°C</p> <p>continuous 70°C / peak 80°C</p>
Properties and advantages:	<p>Very good physical properties - good abrasion and tear resistance</p> <p>Good resistance to oily plasticizers (new generation phthalate free) and to aliphatic hydrocarbons</p> <p>Moderate resistance to phthalate-type plasticizers</p> <p>Excellent stability under pressure</p> <p>Very smooth surface after grinding</p>	
Chemical resistance:	<p>Acid solutions:</p> <p>Alkaline solutions:</p> <p>Hot water and steam:</p> <p>Ozone:</p> <p>Oil and grease:</p> <p>Aromatic solvents (toluene, benzene,...):</p> <p>Chlorinated solvents:</p> <p>Polar solvents (MEC, ether, acetate,...):</p>	<p>Moderate</p> <p>Good</p> <p>Moderate</p> <p>Very good</p> <p>Excellent</p> <p>Moderate</p> <p>Not suited</p> <p>Not suited</p>
Recommended cleaning products:	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, turpentine, white spirit	
Remark:	Temperature wet = in proximity of plasticizers from the produced PVC and soft plastics	