

# MultiCoat-SB



<b>Cover Type:</b>	Rubber	
<b>Possible applications:</b>	<p>Metals and metal packaging industry : applicator rollers and wheels for primer coating, lacquering, varnishing and chemical coating</p> <p>Flexo printing.</p> <p>Wood and wood laminate : varnishing rollers, glue applicators</p> <p>Conversion of paper and film – adhesive and release stock : primer, glue and silicone applicator rollers and sleeves</p> <p>All converting of (printed) paper, board, film and flexible packaging : applicator, coater and (UV) varnishing rollers and sleeves, backing rollers and sleeves</p>	
<b>Hardness Range:</b>	35, 45, 55, 65, 75, 80 Shore A	
<b>Available Colours:</b>	green	
<b>Recommended Cover Thickness:</b>	min. 15 mm - max. 30 mm	
<b>Temperature resistance:</b>	Dry: Wet:	continuous 120°C / peak 130°C continuous 80°C / peak 90°C
<b>Properties and advantages:</b>	<p>Good physical properties</p> <p>Excellent resistance to polar solvents (MEC, acetates, alcohols...)</p> <p>Very good surface wetting and transfer properties</p> <p>High purity and homogeneity</p> <p>Easy to grind and to groove</p>	
<b>Chemical resistance:</b>	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...):	Very good Very good Very good Excellent Not suited Not suited Not suited Excellent
<b>Recommended cleaning products:</b>	(Warm) water, soap, detergent, acid/alkaline cleaners, polar solvents : MEK, alcohol, acetate...	