

MultiGraf-SB



Cover Type:	Rubber	
Possible applications:	Production and conversion of plastic film, flexible packaging, (card)board, tape, labels, adhesives and aluminium foil. Back-up rollers for solventless and solvent based coating and lamination processes. Rotogravure impression rollers for flexible packaging.	
Hardness Range:	65, 75, 80 Shore A	
Available Colours:	green	
Recommended Cover Thickness:	min. 10 mm - max. 20 mm	
Temperature resistance:	Dry: Wet:	continuous 110°C / peak 125°C continuous 80°C / peak 90°C
Properties and advantages:	Excellent resistance to polar solvents (MEK, ethyl acetate, alcohols). Outstanding surface properties in contact with various web types : paper, board, plastic film, aluminium. Very good overall physical properties and abrasion resistance. High purity and homogeneity	
Chemical resistance:	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...): Alcohols (ethanol, IPA,...):	Very good Very good Very good Excellent Not suited Not suited Not suited Excellent Excellent
Recommended cleaning products:	Polar solvents (MEK, ethyl acetate, alcohol...), detergents - avoid hydrocarbons !	