

Hannecoil-XP



Cover Type:	Polyurethane	
Possible applications:	Elastic mandrel sleeves for winding and unwinding of metal coils (steel, stainless steel, aluminium and non-ferrous coils) Dimensions and finish can be adapted to any specific need : adaptor sleeves, protective sleeves, grip improvement, evacuation of water or oil etc.	
Hardness Range:	70, 80 Shore A	
Available Colours:	green	
Recommended Cover Thickness:	min. 5 mm - max. 100 mm	
Temperature resistance:	Dry: Wet:	continuous 80°C / peak 90°C continuous 40°C / peak 50°C
Properties and advantages:	Excellent elastic behaviour - low permanent deformation in use Excellent physical properties, tear-, cut-in and abrasion resistance Excellent resistance to grease and to (mineral) oil	
Chemical resistance:	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...): Alcohols (ethanol, IPA,...):	Not suited Not suited Not suited Moderate Excellent Moderate Not suited Not suited Moderate
Recommended cleaning products:	Water, soap & detergents, fuel, Solvesso, turpentine – with moderation: alcohol based cleaners	