

MetalClean-XP



Cover Type:	Special rubber
Possible applications:	Metal strip industry : sink and squeegee rollers for all alkaline cleaning environments up to 95 °C Metal strip industry : sink and squeegee rollers for acid cleaning environments up to 90 °C Metal strip industry : squeegee, detour, hold-down and pressure rolls in all water-based chemical environments
Hardness Range:	75, 85, 90 Shore A
Recommended Cover Thickness:	min. 15 mm - max. 25 mm
Temperature resistance:	Dry: continuous 115°C / peak 125°C Wet: continuous 85°C / peak 95°C
Properties and advantages:	Overall excellent chemical resistance to alkaline, acid and oxydative products Good resistance to mineral, vegetable and synthetic oils. Fair resistance to kerosine and fuels Very good resistance to vapour penetration (high temperature chemical environments) Good physical properties, abrasion resistance, tear and cut-in resistance
Chemical resistance:	Acid solutions: Very good Alkaline solutions: Excellent Hot water and steam: Very good Ozone: Excellent Oil and grease: Good Aromatic solvents (toluene, benzene,...): Moderate Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Not suited
Recommended cleaning products:	(Warm) water, soap, industrial cleaners and detergents, alcohol, acid and alkaline cleaners
Remark:	Substancja SVHC w stężeniu powyżej 0,1%: Tlenek ołowiu Informacja ta jest przekazywana zgodnie z artykułem 33 rozporządzenia REACH