

NipFoil-S-AS



Cover Type:	Rubber
Possible applications:	Production of plastic films, adhesives and flexible packaging : nip and press rollers, guiding and conveyor rollers, lamination. Contact and lay-on rollers for winding Nip rollers for corona treaters thanks to high antistatic properties.
Hardness Range:	35, 50, 55, 60, 65, 70, 75, 80, 85, 90 Shore A
Recommended Cover Thickness:	min. 6 mm - max. 25 mm
Temperature resistance:	Dry: continuous 110°C / peak 130°C Wet: continuous 80°C / peak 90°C
Properties and advantages:	Bardzo dobre właściwości mechaniczne i dynamiczne. Neutralne zachowanie w kontakcie z wszelkiego rodzaju foliami z tworzyw sztucznych. Doskonała odporność na rozpuszczalniki polarne. Nie zalecany w kontakcie z olejami i smarami
Specific characteristics:	Antistatic
Chemical resistance:	Acid solutions: Excellent Alkaline solutions: Excellent Hot water and steam: Very good Ozone: Excellent Oil and grease: Not suited Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Excellent Alcohols (ethanol, IPA,...): Excellent Ageing resistance: Excellent
Recommended cleaning products:	(Hot) water, acid and alkaline cleaners, IPA and alcohol, MEC, ether, ethyl acetate

NipFoil-S-AS