

# PressoGraf-SB



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	Pressure roll for rotogravure in flat cardboard industry Pressure roll for rotogravure in PVC industry, plastic film industry etc... Any kind of roll when antistatic properties are necessary
<b>Hardness Range:</b>	70, 75, 80, 85, 90 Shore A
<b>Available Colours:</b>	black
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 25 mm
<b>Temperature resistance:</b>	Dry: continuous 110°C / peak 130°C Wet: continuous 80°C / peak 100°C
<b>Properties and advantages:</b>	Excellent resistance to water, ozone and bad weather conditions Very good resistance to ketone solvents and acetate Low resistance to oil and grease Very good resistance to mechanical sollicitations Good cut resistance
<b>Specific characteristics:</b>	Antistatic
<b>Chemical resistance:</b>	Acid solutions: Excellent Alkaline solutions: Excellent Hot water and steam: Very good Ozone: Excellent Oil and grease: Not suited Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Very good
<b>Recommended cleaning products:</b>	Water or compatible solvents