

# PressoGraf-SB



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	Production and conversion of plastic film, PVC, flexible packaging, (card)board, tape, labels, adhesives and aluminium foil : rollers where solvent resistance and antistatic properties are required  Rollers for lamination, both solventless and solvent based - cold and hot lamination  Backing rollers for (hot melt) glue application, printing and coating  Cover quality adapted for composite sleeves
<b>Hardness Range:</b>	70, 75, 80, 85, 90 Shore A
<b>Available Colours:</b>	black
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 25 mm
<b>Temperature resistance:</b>	Dry: continuous 110°C / peak 130°C Wet: continuous 80°C / peak 95°C
<b>Properties and advantages:</b>	Good mechanical properties, good pressure resistance with stable nip  Good and stable electrical conductivity (antistatic properties)  Excellent resistance against polar solvents, like MEC and ethyle acetate
<b>Specific characteristics:</b>	Antistatic
<b>Chemical resistance:</b>	Acid solutions: Very good Alkaline solutions: Very good Hot water and steam: Very good Ozone: Excellent Oil and grease: Not suited Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Excellent Alcohols (ethanol, IPA,...): Excellent Ageing resistance: Excellent
<b>Recommended cleaning products:</b>	Polar solvents (MEK, ethyl acetate, alcohol...), detergents - avoid hydrocarbons !