MultiCoat-SB-AS

Bezugstyp:	Gummi
Mögliche Anwendungen:	Metals and metal packaging industry : applicator rollers and wheels for primer coating, lacquering, varnishing and chemical coating Wood and wood laminate : varnishing rollers, glue applicators Conversion of paper and film – adhesive and release stock : primer, glue and silicone applicator rollers and sleeves All converting of (printed) paper, board, film and flexible packaging : applicator, coater and (UV) varnishing rollers and sleeves, backing rollers and sleeves
Härtebereich:	35, 50, 55, 60, 65, 70, 75 Shore A
Erhältliche Farben:	schwarz
Temperaturbeständigkeit:	trocken — kontinuierlich 110°C / Höchstwert 125°C naß — kontinuierlich 80°C / Höchstwert 90°C
Eigenschaften und Vorteile:	Good physical properties Excellent resistance to polar solvents (MEC, acetates, alcohols…) Very good surface wetting and transfer properties High purity and homogeneity Easy to grind and to groove Antistatic
Spezifische Eigenschaften:	Antistatisch

Chemische Widerstand:

Säuren:	Sehr gut
Basen:	Sehr gut
Heißwasser und Dampf:	Sehr gut
Ozon:	Ausgezeichnet
Öle und Fette:	Nicht geeignet
Aromatische Lösemittel (Toluol, Benzol,...):	Nicht geeignet
Chlorhaltige Lösemittel:	Nicht geeignet
Polare Lösemittel (MEK, Ether, Acetat,...):	Ausgezeichnet

Empfohlene Reinigungsmittel:	(Heiss)Wasser, Seifen und Waschmittel, saure und basische Reiniger, Alkohole, MEK, Acetat