

MultiGraf-SB-AS



Cover Type: Rubber

Possible applications: Production and conversion of plastic film, PVC, flexible packaging, (card)board, tape, labels, adhesives and aluminium foil

Back-up rollers for solventless and solvent based coating and lamination processes

Hardness Range: 60, 65, 70, 75, 80, 85, 90 Shore A

Available Colours: black

Recommended Cover Thickness: min. 12 mm - max. 20 mm

Temperature resistance: Dry: continuous 110°C / peak 125°C
Wet: continuous 80°C / peak 90°C

Properties and advantages: Excellent resistance to polar solvents (MEK, ethyl acetate, alcohols)

Outstanding surface properties in contact with various web types : paper, board, plastic film, aluminium

Very good overall physical properties and abrasion resistance

High purity and homogeneity

Good antistatic properties

Specific characteristics: Antistatic

Chemical resistance:	Acid solutions:	Very good
	Alkaline solutions:	Very good
	Hot water and steam:	Very good
	Ozone:	Excellent
	Oil and grease:	Not suited
	Aromatic solvents (toluene, benzene,...):	Not suited
	Chlorinated solvents:	Not suited
Polar solvents (MEC, ether, acetate,...):	Excellent	

Recommended cleaning products: Polar solvents (MEK, ethyl acetate, alcohol...), detergents - avoid hydrocarbons !