

MultiGraf-SB-AS



Cover Type:	Rubber
Possible applications:	Production and conversion of plastic film, PVC, flexible packaging, (card)board, tape, labels, adhesives and aluminium foil Back-up rollers for solventless and solvent based coating and lamination processes Rotogravure impression rollers for flexible packaging and décor printing
Hardness Range:	60, 65, 70, 75, 80, 85, 90 Shore A
Available Colours:	black
Recommended Cover Thickness:	min. 12 mm - max. 20 mm
Temperature resistance:	Dry: continuous 110°C / peak 125°C Wet: continuous 80°C / peak 90°C
Properties and advantages:	Excellent resistance to polar solvents (MEK, ethyl acetate, alcohols) Outstanding surface properties in contact with various web types : paper, board, plastic film, aluminium Very good overall physical properties and abrasion resistance High purity and homogeneity Good antistatic properties
Specific characteristics:	Antistatic
Chemical resistance:	Acid solutions: Very good Alkaline solutions: Very good Hot water and steam: Very good Ozone: Excellent Oil and grease: Not suited Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Excellent
Recommended cleaning products:	Polar solvents (MEK, ethyl acetate, alcohol...), detergents - avoid hydrocarbons !