

# MultiGraf-SB-AS



<b>Cover Type:</b>	Rubber	
<b>Possible applications:</b>	Production and conversion of plastic film, PVC, flexible packaging, (card)board, tape, labels, adhesives and aluminium foil  Back-up rollers for solventless and solvent based coating and lamination processes	
<b>Hardness Range:</b>	60, 65, 70, 75, 80, 85, 90 Shore A	
<b>Recommended Cover Thickness:</b>	min. 12 mm - max. 20 mm	
<b>Temperature resistance:</b>	Dry: Wet:	continuous 110°C / peak 125°C continuous 80°C / peak 90°C
<b>Properties and advantages:</b>	Excellent resistance to polar solvents (MEK, ethyl acetate, alcohols)  Outstanding surface properties in contact with various web types : paper, board, plastic film, aluminium  Very good overall physical properties and abrasion resistance  High purity and homogeneity  Good antistatic properties	
<b>Specific characteristics:</b>	Antistatic	
<b>Chemical resistance:</b>	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...):	Very good Very good Very good Excellent Not suited Not suited Not suited Excellent
<b>Recommended cleaning products:</b>	Polar solvents (MEK, ethyl acetate, alcohol...), detergents - avoid hydrocarbons !	