

# FoilSpread-AS



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	Contact rollers, winding rollers, spreading rollers and all applications where soft and constant contact is needed : thin films, stretchnig films
<b>Hardness Range:</b>	30, 35, 45, 50 Shore A
<b>Available Colours:</b>	black
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 25 mm
<b>Temperature resistance:</b>	Dry: continuous 100°C / peak 110°C Wet: continuous 70°C / peak 80°C
<b>Properties and advantages:</b>	Very good physical properties, good tear and cut-in resistance. Excellent resistance to mineral, vegetable and synthetic oils. Very good resistance to kerosine and fuels. Good resistance to diluted acids and to alkaline solutions. Antistatic.
<b>Specific characteristics:</b>	Antistatic
<b>Chemical resistance:</b>	Acid solutions: Good Alkaline solutions: Good Hot water and steam: Good Ozone: Very good Oil and grease: Excellent Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Not suited
<b>Recommended cleaning products:</b>	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, terpentine, white spirit