

FoilSpread-AS



| | |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cover Type: | Rubber |
| Possible applications: | Contact rollers, winding rollers, spreading rollers and all applications where soft and constant contact is needed : thin films, stretchnig films |
| Hardness Range: | 30, 35, 45, 50 Shore A |
| Available Colours: | black |
| Recommended Cover Thickness: | min. 10 mm - max. 25 mm |
| Temperature resistance: | Dry: continuous 100°C / peak 110°C Wet: continuous 70°C / peak 80°C |
| Properties and advantages: | Very good physical properties, good tear and cut-in resistance. Excellent resistance to mineral, vegetable and synthetic oils. Very good resistance to kerosine and fuels. Good resistance to diluted acids and to alkaline solutions. Antistatic. |
| Specific characteristics: | Antistatic |
| Chemical resistance: | Acid solutions: Good Alkaline solutions: Good Hot water and steam: Good Ozone: Very good Oil and grease: Excellent Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Not suited |
| Recommended cleaning products: | (Hot) water, soap, most industrial cleaners, alcohol, light fuel, terpentine, white spirit |