

# MetalSqueeze-AR



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	Production of steel, stainless steel, aluminium and non-ferrous strip : - Squeegee and hold-down rollers in chemical environment - Sink rolls  Specifically suited for acid environment and for water rinse, quench and cool-down
<b>Hardness Range:</b>	60, 70, 75, 80 Shore A
<b>Available Colours:</b>	black
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 25 mm
<b>Temperature resistance:</b>	Dry: continuous 110°C / peak 120°C Wet: continuous 90°C / peak 95°C
<b>Properties and advantages:</b>	Good physical properties  Very good resistance to most (concentrated) acid and oxydative environments, also at high temperature
<b>Chemical resistance:</b>	Acid solutions: Excellent Alkaline solutions: Excellent Hot water and steam: Excellent Ozone: Excellent Oil and grease: Not suited Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Very good Alcohols (ethanol, IPA,...): Excellent
<b>Recommended cleaning products:</b>	(Hot) water, acid and alkaline cleaners, IPA and alcohol, MEC, ether, ethyl acetate