



<b>Cover Type:</b>	Special polyurethane	
<b>Possible applications:</b>	Suction Grooved Press Roll	
<b>Hardness Range:</b>	5, 10, 15, 20, 25, 30, 35 PJ	
<b>Available Colours:</b>	green	
<b>Recommended Cover Thickness:</b>	max. 25 mm	
<b>Temperature resistance:</b>	Dry:	continuous 80°C / peak 110°C
<b>Doctoring:</b>	HDPE blade at 1 to 2 mm from surface or 18 deg & 50 to 70 N/m if loaded, HDPE foil blade 10 deg, 50 to 70 N/m Dry doctoring is prohibited	
<b>Possible surface design:</b>	P (Plain), S (Suction), BD (Blind Drilled), G (Grooved) & combined SBD, SG, SBDG, BDG	
<b>Max. linear load:</b>	Depending on operating conditions and nip rolls Ø (to be validated by Hannecard in case of doubt)	
<b>Chemical resistance:</b>	Acid solutions:	Not suited
	Alkaline solutions:	Not suited
	Hot water and steam:	Not suited
	Ozone:	Good
	Oil and grease:	Very good
	Chlorinated solvents:	Not suited
	Polar solvents (MEC, ether, acetate,...):	Not suited
<b>Recommended cleaning products:</b>	Good resistance to standard chemicals normally used in paper	
<b>Remark:</b>	Reference list available on demand	