



Cover Type:	Rubber	
Possible applications:	<p>Diverse applications in a lot of industrial areas : textile, packaging, (card)board, plastic film, PVC and décor, converting, glass, wood etc.</p> <p>Conveyor, winding, nip, deflector, steering and lamination rollers</p> <p>Production of metal strip: pinch rolls, hold-down rolls, steering, bridle and detour rolls, conveyor rollers, oil distribution and wipe-off rolls, squeegee rolls in different environments</p> <p>Paraffin and wax applicators</p> <p>Rollers and wheels in contact with oil, fuel or grease, even at higher temperature</p>	
Hardness Range:	65, 75, 80, 85, 90 Shore A	
Available Colours:	beige	
Recommended Cover Thickness:	min. 10 mm - max. 25 mm	
Temperature resistance:	Dry: Wet:	continuous 100°C / peak 110°C continuous 70°C / peak 80°C
Properties and advantages:	<p>Excellent resistance to mineral and vegetable oil, fuel, grease and (animal) fat</p> <p>Very good physical properties, tear and abrasion resistance, good elasticity and resilience</p> <p>Non-staining in contact with delicate substrates</p> <p>Good and stable grip in contact with most substrates</p> <p>Very good squeegee and wipe-off behaviour</p>	
Chemical resistance:	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...): Alcohols (ethanol, IPA,...):	Moderate Good Moderate Good Excellent Moderate Not suited Not suited Very good
Recommended cleaning products:	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, terpentine, white spirit	

Remark:

Suited for NaOH and KOH solutions up to 5 % concentration, at temperature of max. 75 °C
