



<b>Cover Type:</b>	Silicone rubber	
<b>Possible applications:</b>	Rollers and wheels submitted to high temperature and/or in conditions where non-stick properties are required Plastic film production : conveyor, deflector and nip rollers at high temperature Metal industrie - coil processes : deflectorrolls at oven/furnace entry and exit Backing rollers and wheels for hot lamination, calendering, glue application and hot-melt processes Hot glue applicators	
<b>Hardness Range:</b>	40, 50, 60, 70, 75, 80 Shore A	
<b>Available Colours:</b>	grey	
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 20 mm	
<b>Temperature resistance:</b>	Dry:	continuous 200°C / peak 220°C
	Wet:	continuous 80°C / peak 90°C
<b>Properties and advantages:</b>	Pure and homogeneous silicone cover Very good non-stick properties, glue repellent Average physical properties, not suited for applications submitted to high mechanical load Gut resistance against hot water and vapour, against alcohol and against mineral oil	
<b>Specific characteristics:</b>	Glue repellent/non-stick properties	
<b>Chemical resistance:</b>	Acid solutions:	Moderate
	Alkaline solutions:	Good
	Hot water and steam:	Very good
	Ozone:	Excellent
	Oil and grease:	Good
	Aromatic solvents (toluene, benzene,...):	Not suited
	Chlorinated solvents:	Moderate
	Polar solvents (MEC, ether, acetate,...):	Moderate
	Alcohols (ethanol, IPA,...):	Very good
	Ageing resistance:	Very good
<b>Recommended cleaning products:</b>	(Hot) water, steam, soap and detergents, industrial cleaners, alcohol based	

cleaners

---