



Cover Type:	Composite	
Possible applications:	Breast roll, Forming roll, Wire Guide roll, Table roll, Felt roll, Felt Guide roll, Drying Wire roll, Drying Felt roll, Paper Sheet roll in dry or wet environment	
Hardness Range:	90 Shore D	
Available Colours:	blue	
Recommended Cover Thickness:	min. 5 mm - max. 15 mm	
Temperature resistance:	Dry:	continuous 120°C / peak 130°C
Properties and advantages:	<p>Very high-end composite</p> <p>Doctorability</p> <p>Optimum resistance to wear and abrasion</p> <p>High temperature resistance</p> <p>Fine surface condition (Ra < 1 microns) to protect the wire and better doctoring (self-lubricating water film on the surface)</p>	
Doctoring:	Steel, fiberglass or plastic blades	
Chemical resistance:	<p>Acid solutions:</p> <p>Alkaline solutions:</p> <p>Hot water and steam:</p> <p>Ozone:</p> <p>Oil and grease:</p> <p>Chlorinated solvents:</p> <p>Polar solvents (MEC, ether, acetate,...):</p> <p>Ageing resistance:</p>	<p>Excellent</p> <p>Very good</p> <p>Excellent</p> <p>Excellent</p> <p>Very good</p> <p>Good</p> <p>Good</p> <p>Excellent</p>
Recommended cleaning products:	Good resistance to standard chemicals normally used in paper machines	
Remark:	Reference list available on demand	