


# HannElast-XP



<b>Cover Type:</b>	Rubber
<b>Possible applications:</b>	Wheels, pulleys and rollers for conveying and driving in all industrial environments  Conveyor rollers for mining and for transport of ore, minerals and raw materials  Rollers submitted to abrasion, in dry and humid environment, but in absence of oil and grease  Textile and flooring industry : winder rolls, drive rolls for cutting and packaging
<b>Hardness Range:</b>	65, 70 Shore A
<b>Available Colours:</b>	black, beige
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 25 mm
<b>Temperature resistance:</b>	Dry: continuous 80°C / peak 90°C Wet: continuous 60°C / peak 70°C
<b>Properties and advantages:</b>	Very good abrasion resistance, overall very good physical properties  High friction coefficient, excellent grip  Good resistance to acid and alkaline solutions up to 50 °C – good resistance to alcohol based solvents High friction coefficient, excellent grip
<b>Chemical resistance:</b>	Acid solutions: Good Alkaline solutions: Good Hot water and steam: Not suited Ozone: Moderate Oil and grease: Not suited Aromatic solvents (toluene, benzene,...): Not suited Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Moderate
<b>Recommended cleaning products:</b>	Water, warm water, soap and detergents, alcohol based cleaners, acid based cleaners