

BupFoil-HP



Cover Type:	Special rubber	
Possible applications:	Conversion of flexible products : nip rollers, counterparts, steering rollers at high temperature and load. Production of (bi-oriented) plastic film : MDO nip rollers, stretching and orienter rollers. Production of flexible packaging, plastic film and adhesives : laminator and calender rollers, specifically under high load and/or temperature. Production of metal sheet, foil and adhesives : furnace entry/exit rollers, ironing rollers, sealing rollers for vacuum environment.	
Hardness Range:	87, 92, 95, 96 Shore A	
Available Colours:	black	
Recommended Cover Thickness:	min. 10 mm - max. 20 mm	
Temperature resistance:	Dry:	continuous 125°C / peak 150°C
	Wet:	continuous 80°C / peak 90°C
Properties and advantages:	Excellent stability under high load and elevated temperature. Very good abrasion and tear resistance. Good response to dynamic load and heat build-up, even at high temperature. Excellent resistance to oil and grease - Limited resistance to polar solvents, like MEC, acetates and ether.	
Chemical resistance:	Acid solutions:	Moderate
	Alkaline solutions:	Good
	Hot water and steam:	Good
	Ozone:	Very good
	Oil and grease:	Excellent
	Chlorinated solvents:	Not suited
	Polar solvents (MEC, ether, acetate,...):	Not suited
Recommended cleaning products:	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, turpentine, white spirit	