


HanneTop-L



Cover Type:	Special rubber
Possible applications:	All industries : rollers, wheels & parts submitted to high mechanical and/or dynamical load at elevated temperature Furnace entry/exit rollers - conveyor, nip, backing, laminator rollers Rollers & wheels in contact with oil, petroleum or kerosene at high temperature
Hardness Range:	70, 85, 95 Shore A
Available Colours:	green, blue
Recommended Cover Thickness:	min. 15 mm - max. 30 mm
Temperature resistance:	Dry: continuous 145°C / peak 160°C Wet: continuous 80°C / peak 90°C
Properties and advantages:	Very high mechanical and dynamical properties - high load resistance Special high-load and high-temperature bonding technology High temperature resistance (up to max 160 °C) Excellent resistance to grease, mineral oil, petroleum and kerosene Light colour - non staining
Chemical resistance:	Acid solutions: Moderate Alkaline solutions: Good Hot water and steam: Good Ozone: Very good Oil and grease: Excellent Aromatic solvents (toluene, benzene,...): Moderate Chlorinated solvents: Not suited Polar solvents (MEC, ether, acetate,...): Not suited Alcohols (ethanol, IPA,...): Very good Ageing resistance: Excellent
Recommended cleaning products:	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, turpentine, white spirit