

PureDrive-AS



Cover Type:	Polyurethane	
Possible applications:	Rollers submitted to high load and/or high abrasion, rollers where cut-in resistance is important and where antistatic properties are required Plastic film, flexible packaging, glass fibre & non-woven and aluminium industry : nip, counterpress, laminator rollers, detour and tensioning rollers	
Hardness Range:	70, 80, 90, 95 Shore A	
Available Colours:	black	
Recommended Cover Thickness:	min. 10 mm - max. 25 mm	
Temperature resistance:	Dry:	continuous 80°C / peak 90°C
	Wet:	continuous 40°C / peak 50°C
Properties and advantages:	Excellent abrasion, tear and cut-in resistance Resistant to high load applications, excellent impact resistance Easy to clean and to maintain	
Specific characteristics:	Antistatic	
Chemical resistance:	Acid solutions:	Not suited
	Alkaline solutions:	Moderate
	Hot water and steam:	Not suited
	Ozone:	Good
	Oil and grease:	Very good
	Aromatic solvents (toluene, benzene,...):	Not suited
	Chlorinated solvents:	Not suited
	Polar solvents (MEC, ether, acetate,...):	Not suited
	Alcohols (ethanol, IPA,...):	Good
Recommended cleaning products:	(Tepid) water, soap, industrial cleaners, cleaning fuel, terpentine, with limited use : alcohol	