


# Hannethane-D



<b>Cover Type:</b>	Polyurethane	
<b>Possible applications:</b>	Specifically recommended for looper rollers in the metals industry  Rollers submitted to heavy abrasion, where the inspection can only be done from a distance	
<b>Hardness Range:</b>	90, 95 Shore A	
<b>Available Colours:</b>	brown	
<b>Recommended Cover Thickness:</b>	min. 10 mm - max. 20 mm	
<b>Temperature resistance:</b>	Dry: Wet:	continuous 90°C / peak 100°C continuous 50°C / peak 60°C
<b>Properties and advantages:</b>	Double layer/double colour covering with a bright yellow base layer (4 mm), that can visually be used as abrasion witness  This covering solutions allow to verify the abrasion on the roller cover in a safe way and from a distance  Other properties identical to Hannethane-S : polyurethane cover with excellent abrasion resistance and very good overall physical properties	
<b>Chemical resistance:</b>	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,...): Chlorinated solvents: Polar solvents (MEC, ether, acetate,...):	Moderate Moderate Not suited Good Very good Not suited Not suited Not suited
<b>Recommended cleaning products:</b>	(Tepid) water, soap, industrial cleaners, cleaning fuel, terpentine, with limited use : alcohol	