## Optidraw



Cover Type:	Rubber	
Possible applications:	<ul> <li>Production of metal strip : pinch rolls, hold-down rolls, steering, bridle and detour rolls, conveyor rollers, oil distribution and wipe-off rolls, squeegee rolls in different environments</li> <li>Diverse applications in a lot of industrial areas : textile, packaging, (card)board, plastic film, converting, glass, wood etc.</li> </ul>	
	Rollers and wheels in contact with oil, fuel o	r grease, even at higher temperature
Hardness Range:	65 Shore A	
Available Colours:	beige	
Recommended Cover Thickness:	min. 10 mm - max. 25 mm	
Temperature resistance:		ntinuous 90°C / peak 110°C ntinuous 60°C / peak 80°C
Properties and advantages:	Excellent resistance to mineral and vegetal oil, fuel, grease and (animal) fat	
	Very good physical properties, tear and abrasion resistance, good elasticity and resilience	
	Non-staining in contact with delicate substrates	
	Good and stable grip in contact with most substrates	
	Very good squeegee and wipe-off behavior	
Chemical resistance:	Acid solutions: Alkaline solutions: Hot water and steam: Ozone: Oil and grease: Aromatic solvents (toluene, benzene,): Chlorinated solvents: Polar solvents (MEC, ether, acetate,):	Good Very good Good Excellent Moderate Not suited Not suited
Recommended cleaning products:	(Hot) water, soap, most industrial cleaners, alcohol, light fuel, terpentine, white spirit	

